



HKM-CF

Commercial HVLS Fan



COMMERCIAL HVLS

Permanent-Magnet Synchronous Motor

Blade color options

Grey



Control Panel

Product Descriptions

HKM Commercial HVLS fan was developed independently by factory technicians. The fan brings huge airflow continuously and soon forming an air circulation, effectively in wide areas. It equipped with an excellent effect of temperature rising at around 40 °C. It's gearless, compared to gear motor HVLS fan, it is more silent, fully maintenance-free, and has less space limitation for installation.

Product Item

Product code	Product size	
HKM-CF-5500	5.5 meters	18ft
HKM-CF-4600	4.6 meters	15ft
HKM-CF-3700	3.7 meters	12ft

Electrical options

- 220V /1P
- 220V /3P
- 380V /3P

Technical Data

Model	HKM-CF-3700	HKM-CF-4600	HKM-CF-5500
Diameter	3.7m	4.6m	5.5m
RPM	65	60	55
Airflow (m ³ /min)	8500	9000	9800
Max Coverage	650 m ²	850 m ²	900
Rated Power		600W	
Motor Frequency		27Hz	
Torque		70 N·m	
Motor weight		23 kgs	
Efficiency		86%	
Pole number		40	
Noise		≤40 dBA	
Protection		IP65	
Insulation		Clase F	
Temperature rise		40 °C	

Call Now

5503 8458

www.hkmisting.com



HKM-CF

INDUSTRIAL HVLS Fan



INDUSTRIAL HVLS

Permanent-Magnet Synchronous Motor

Blade color options

Grey

Product Descriptions

HKM PMSM HVLS Fan was developed by HKM Technicians allied with China Top 3 universities, Tsinghua & Zhejiang University. The fan brings huge airflow continuously and soon forming an air circulation, effectively in wide areas. It equipped with an excellent effect of temperature rising at around 40°C. It's gearless, compared to gear motor HVLS fan, it is more silent, fully maintenance-free, and has less space limitation for installation.



Control Panel

Product Items

Product code	Product size	
HKM-CF-7300	7.3 meters	24ft
HKM-CF-6400	6.4 meters	21ft

Electrical options

- 220V /1P
- 220V /3P
- 380V /3P

Technical Data

	HKM-CF-6400	HKM-CF-7300
Diameter	6.4m	7.3m
RPM	0~54	0~54
Airflow (m ³ /min)	14000	15500
Max Coverage	1480 m ²	1800 m ²
Weight	130 kg	138 kg
Rated Power	1500W	
Voltage	380V / 220V ± 10%	
Rated Current	3.2A / 4.0A	
Motor Frequency	13.5 Hz	
Torque	265 N·m	
Motor Weight	61 kg	
Efficiency	91%	
Pole number	30	
Noise	≤40 dBA	
Protection	IP65	
Insulation	Clase F	
Temperature rise	40 °C	

Call Now

5503 8458

www.hkmisting.com