

01



吊頂除濕機
隱形戰士 除濕無影

02



| 型號 | DE05-26A | DE05-36A | DE05-56A | DE05-96A | DE-05-136A |
|---------|--------------------------|--------------------------|----------------------|----------------------|-----------------------|
| 除濕量 | 26L/D | 36L/D | 56L/D | 96L/D | 136L/D |
| 電壓 / 頻率 | 220V/50Hz | 220V/50Hz | 220V/50Hz | 220V/50Hz | 220V/50Hz |
| 最大功率 | 380W | 700W | 800W | 980W | 1100W |
| 輸入電流 | 2A | 3A | 3.5A | 4.5A | 5A |
| 風量 | 270-320m ³ /h | 480-560m ³ /h | 750m ³ /h | 980m ³ /h | 1400m ³ /h |
| 適用溫度 | 5-38°C | 5-38°C | 5-38°C | 5-38°C | 5-38°C |
| 機身尺寸 | 650*330*255mm | 782*390*340mm | 782*390*340mm | 827*510*442mm | 827*510*442mm |
| 適用面積 | 20-40m ² | 40-60m ² | 60-80m ² | 90-120m ² | 120-150m ² |

Air-A 系列 中央管道抽濕系統

中央管道抽濕系統

室內潮濕空氣經過制冷系統(壓縮機,蒸發器,冷凝器)凝結成水由水管排出機外,產生乾燥的空氣輸送到所需區域,如此循環使室內濕度降低,達到乾爽效果。




PRODUCT FEATURES

產品特點

優質傳感器:±3%濕度精確控制,任意設定

超靜音設計:整體機身78處靜音處理,確保靜音效果

搭載Panasonic 壓縮機,高效穩定運行,精準抽濕



DE-05-A系列



DE-05-140A旗艦機

| 型號 | DE-05-A-30L | DE-05-A-40L | DE-05-A-60L | DE-05-A-80L | DE-05-A-100L | DE-05-A-140L |
|---------|----------------------|----------------------|----------------------|----------------------|-----------------------|-----------------------|
| 電壓 | 220V/50Hz | | | | | |
| 抽濕量 | 30L/D | 40L/D | 60L/D | 80L/D | 100L/D | 140L/D |
| 適用面積 | 10-40m ² | 40-60m ² | 60-80m ² | 80-100m ² | 100-150m ² | 150-200m ² |
| 抽濕量測試環境 | T=30°C, RH=80% | | | | | |
| 最大功率 | 510W | 580W | 980W | 1150W | 1350W | 1450W |
| 風量 | 280m ³ /h | 380m ³ /h | 500m ³ /h | 600m ³ /h | 950m ³ /h | 1200m ³ /h |
| 機外餘壓 | 50pa | 50pa | 80pa | 80pa | 100pa | 100pa |
| 室內出風口 | 100mm | 100mm | 150mm | 150mm | 200mm | 200mm |
| 室內進風口 | 100mm | 100mm | 150mm | 150mm | 200mm | 200mm |
| 過濾裝置 | 初效G4 | 初效G4 | 初效G4 | 初效G4 | 初效G4 | 初效G4 |
| 控制方式 | 智能自動控制器、內置水泵可向上排水 | | | | | |
| 機身尺寸 | 852*429*250mm | 852*429*250mm | 946*489*322mm | 946*489*322mm | 1075*648*376mm | 1075*648*376mm |