



Wet Air Scrubber 濕式空氣洗滌風機

WAS1 Specification:

Dimension	850 x 850 x 1700mm
Power consumption	220V, 50Hz, 600w
Water tank	85L
Airflow	90000m ³ /h

WAS2 Specification:

Dimension	500 x 370 x 880mm
Power consumption	220V, 50Hz, 150W
Water tank	50L
Airflow	14000m ³ /h

WAS1-空氣洗滌風機



WAS2-空氣洗滌風機

EucalyPower
除臭殺菌濾芯
建議6個月換一次

EucalyPower 安全測試證書



除臭濾芯

Sterilization Testing

Kill Escherichia coli **>99.999%**

Kill Staphylococcus aureus **>99.999%**

Kill Candida albicans **97.902%**

Biosafety Testing

Inhalation Safety Testing

Oral Ingestion Safety Testing


Skin Safety Testing

Odor Neutralization Testing

H₂S (Hydrogen Sulfide) Testing

NH₃ (Ammonia) Testing

CH₂O (Formaldehyde) Testing



Call Now
5503 8458

www.hkmisting.com

Island West Refuse Transfer Station



Island East Refuse Transfer Station



Nim Wan Refuse Transfer Station



Housing estate garbage room



Call Now
5503 8458

www.hkmisting.com

After using the Wet Air Scrubber at T.S.T. Shopping Mall Septic tank, we observed the following results.



T.S.T. Shopping Mall Septic tank

Field Testing

Before



NH₃ 29.9ppm
H₂S 75ppm

30mins

After



NH₃ 9.3ppm
H₂S 27ppm

NH₃ reduction

⬇️ 69%

H₂S reduction

⬇️ 64%

The field testing results show a significant reduction in ammonia (NH₃) and hydrogen sulfide (H₂S) levels after 30 minutes.

Conclusion:

NH₃ levels decreased from 29.9 ppm to 9.3 ppm (a reduction of ~69%).

H₂S levels decreased from 75 ppm to 27 ppm (a reduction of ~64%).

Call Now

5503 8458

www.hkmisting.com